

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**

**THIS PAGE BLANK (USPTO)**

**THIS PAGE BLANK (USPTO)**

PH

000632

HLC  
wo

MAT.

PCT DOSSIER

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification<sup>6</sup> :

G06F 11/10, H04L 12/56

A1

(11) International Publication Number:

WO 95/14971

(43) International Publication Date:

1 June 1995 (01.06.95)

(21) International Application Number: PCT/US94/12033

(22) International Filing Date: 21 October 1994 (21.10.94)

(30) Priority Data:

08/156,857

22 November 1993 (22.11.93)

US

(71) Applicant: MOTOROLA, INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US).

(72) Inventors: DESNOYERS, Peter, Joseph; 162 Pleasant Street, Cambridge, MA 02139 (US). QURESHI, Shahid, Ul, Hao; 24 Indian Ridge Road, Natick, MA 01760 (US).

(74) Agents: PARMELEE, Steven, G. et al.; Motorola Inc., Intellectual Property Depart./DJS, 1303 East Algonquin Road, Schaumburg, IL 60196 (US).


(81) Designated States: AU, CA, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

**Published***With international search report  
With amended claims.*

(54) Title: METHOD AND SYSTEM FOR SYNCHRONIZING ENCODERS AND DECODERS IN COMMUNICATION NETWORKS WHEN ERRORS ARE DETECTED

## (57) Abstract

The method and system (400) synchronize an encoder of an encoder error synchronizer (402) and a decoder of a decoder error synchronizer (404) for data utilizing sequence indicators and error detection information added to the data before transmission. For example, compressed data may be organized into units, a sequence indicator and error detection information added to the compressed data unit (410) and the received units may be synchronized using the sequence indicators and error corrected using the error detection information.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

METHOD AND SYSTEM FOR SYNCHRONIZING ENCODERS AND DECODERS IN  
COMMUNICATION NETWORKS WHEN ERRORS ARE DETECTED

**NETWORKS**

5

**Field of the Invention**

This invention relates to communication systems and in particular to the synchronization of transmitted encoded data  
10 such as compressed data in communication networks.

**Background**

Digital systems typically communicate using packet-  
15 switched digital communication networks. The networks generally include a plurality of nodes that may transmit, receive or forward data. Data to be transmitted is typically organized into units such as frames or cells. The units are sent from one node to another either directly or utilizing one  
20 or more intermediate nodes. The communication channel established between edge nodes in the network is generally termed a virtual circuit.

When data that is sent through the network is  
25 compressed before transmittal, transmission efficiency through the network is increased. Typically, an encoder at a source node may compress data, which is then transmitted and decompressed at a destination node. However, when error(s) occur during transmission, synchronization between the  
30 encoder and the decoder is lost. There is a need for efficient synchronization of transmittal of data through a network.

35

### Brief Descriptions of the Drawings

FIG. 1 is a block diagram of users groups connected to a communication network as is known in the art.

5

FIG. 2 is a flow chart of a first embodiment of steps in accordance with the method of the present invention.

FIG. 3 is a flow chart showing one embodiment of the step of synchronizing an encoder and a decoder when an error is detected (FIG. 2) with greater particularity.

10

FIG. 4 is a block diagram of a first embodiment of a system in accordance with the system of the present invention.

15

FIG. 5 is a flow chart of a second embodiment of steps in accordance with the method of the present invention.

### 20 Detailed Description of a Preferred Embodiment

FIG. 1, numeral 100, is a block diagram of users groups connected to a communication network as is known in the art. Typically, a first user group (102) is operably coupled to a first node (104) of a communication network (106), that is in turn coupled to other nodes (108, 110), and to a receiving node (112) for a second user group (114). Data is exchanged between the first user group and the second user group by transmittal between the first node and the receiving node via connected nodes of the communication network.

25

30

FIG. 2, numeral 200, is a flow chart of an embodiment of steps in accordance with the method of the present invention. The method synchronizes an encoder and decoder of a communication network upon detecting an error. The method

35

includes, for units of encoded data, the steps of: 1) adding to each unit of encoded data, error detection information based on a current unit and at least one previous unit to provide error detect units (202); 2) transmitting said error detect units across the communication network (204); 3) receiving the error detect units (206); 4) detecting error(s) utilizing the error detection information (208), and 5) synchronizing the encoder and decoder upon detecting error(s) (210).

10 In one embodiment the units of encoded data are frames of asynchronous transfer mode (ATM) cells that are transmitted across an ATM communication network. For example, a unit may be selected to be a data unit in an ISDN adaptation layer such as B-ISDN ATM Adaptation Layer 5  
15 (AAL5) of CCITT recommendation I.363.

Error detection information is generally a code sequence added to said unit of encoded data subsequent to encoding the data such as a cyclic redundancy code (CRC), a code sequence  
20 other than a CRC wherein the code sequence is calculated from the encoded data, a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, or a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a previous reset.  
25 Thus, where a code sequence is based on a size of the unit of encoded data, for example, a code sequence may be based on a sequence number or running byte-count.

When encoding and decoding are performed on a sequence  
30 of data frames, the states of the encoder and decoder are often maintained between processing of successive frames without resetting at the beginning of each frame. Therefore, synchronization must be maintained from frame-to-frame. For example, if the communication network drops an entire frame

or mis-orders a sequence of frames, synchronization will be lost. Whereas typical CRCs are based entirely on only a single frame, they are only capable of detecting transmission errors which occur within that frame. They are insufficient  
5 for the purpose of detecting the type of error in which frames are lost entirely or mis-ordered. According to the technique of the present invention, for the purpose of detecting loss of synchronization, the error detection information must be based on the current encoded frame and on at least the previous  
10 encoded frame.

In one embodiment, the encoder responds to receipt of a reset request code sequence by resetting the encoder and generating a reset acknowledgement code sequence to the  
15 decoder. The decoder is reset when it receives the reset acknowledgement code sequence, thereby resynchronizing with the encoder. In this case, the decoder discards frames received after transmission of the reset request code sequence until the reset acknowledgement code sequence is received.

20 In a second embodiment, it is unnecessary for the encoder to explicitly transmit a reset acknowledgement code sequence to the decoder. Instead, the decoder resets itself, including the decoder error detecting circuit at the beginning of each encoded frame until an encoded frame is received that passes  
25 error detection without an error. In this case, the decoder performs error detection, then discards frames received after transmission of the reset request code sequence until a frame passes error detection without an error. The first encoded frame that passes error detection in the decoder without an  
30 error is taken to be the first frame sent by the encoder following the reset of the encoder in response to the reset request code sequence; the encoder and the decoder are then said to be synchronized.



In one embodiment, each successive frame in the sequence of encoded frames is associated with the next value of a frame counter, called a sequence number. In another embodiment, each successive encoded data byte in the sequence of encoded bytes of encoded frames is associated with the next value of a byte counter, called a sequence number. The sequence number for a frame may be concatenated with the CRC for that frame to comprise the error detecting information for that frame. In another embodiment, the sequence number and the CRC are combined by adding them together to comprise the error detection information. In yet another embodiment, the error detection information is a CRC computed for the current frame, where unlike the common practice, the CRC is not reset to a fixed initial value at the beginning of the current frame, but instead the CRC is initialized to the value computed from the previous frame. These and other embodiments of the error detection information are chosen to be simple enough to minimize the cost of implementation, small enough to minimize the cost of transmission over the network, and are sufficiently unique to the particular encoded frame sequence to provide an acceptably high probability of detecting bit-errors and lost or misordered frames.

The communication network includes a plurality of nodes arranged so that a plurality of paths exist among at least some nodes between which said method is practiced. Typically, at least one node may communicate with more than one node at a time. Generally, encoded data may be selected to be compressed data.

Synchronizing the encoder and decoder may be selected to further include: (1) upon detecting an error at decoder, transmitting a reset request code sequence over a reverse channel upon said detecting of error(s) to the encoder, and

where the encoder transmits an acknowledgment code sequence over said communication network to acknowledge reception of said reset request code sequence, one of: a) where the acknowledgment code sequence is received, resetting the decoder, and b) where there is a failure of the acknowledgment code sequence to be received, the decoder transmitting a further reset request code sequence to the encoder, and alternatively, 2) where the decoder resets the timer upon a received unit successfully passing error detection.

FIG. 3, numeral 300, is a flow chart showing one embodiment of the step of synchronizing an encoder and a decoder when an error is detected (FIG. 2) with greater particularity. Each step of synchronizing the encoder and decoder when an error is detected may include (1) detecting of error(s) at the decoder (302), (2) transmitting a reset request code sequence to the encoder, and where selected, setting a timer (304), (3) the encoder's receiving the reset request code sequence (306), (4) the encoder's resetting and generating a reset acknowledgment (308), (5) the decoder's waiting (310) for one of: expiration of the timer and receiving the reset acknowledgment, (6) upon expiration of the time without receiving the reset acknowledgment, recycling to sending the reset request and starting the timer (304), and, (7) upon receiving the reset acknowledgment, resetting the decoder (312). The reset request code sequence initiates resetting of the encoder and sending acknowledgment (ACK) of receipt of the request acknowledgment code sequence to the decoder. Where a timer has been set, the decoder determines whether the timer has expired without the decoder's receiving an acknowledgment from the encoder (306), and where the timer is expired without an acknowledgment, the step of transmitting the reset request to the encoder is repeated. When the timer is unexpired, the decoder determines whether a

reset acknowledgment has been received from the encoder (308). Where there is a failure of the reset acknowledgment to be received, the method recycles to the step of transmitting the reset request to the encoder (304). Where the reset  
5 acknowledgment is received, the decoder is reset (310).

Thus, upon the decoder's detecting an error, the method may include the decoder's transmitting a reset request to the encoder, and where the reset request code sequence is received  
10 at the encoder, resetting the encoder. Here, each step of synchronizing the encoder and decoder further includes one of: (1) where the encoder transmits an acknowledgment code sequence over said communication network to acknowledge reception of said reset request code sequence and the  
15 acknowledgment code sequence is received, resetting the decoder such that the decoder is synchronized with the encoder, and (2) where the decoder is reset upon the decoding of each encoded data unit until a received unit successfully passed error detection. In addition, said step of synchronizing  
20 the encoder and decoder upon detecting error(s) may be selected to further include one of: (1) transmitting a second reset request code sequence over a reverse channel upon failure to receive said acknowledgment code sequence upon an expiration of a timer, and (2) transmitting a second reset  
25 request code sequence over said reverse channel upon failure of at least one received unit to successfully pass error detection upon an expiration of said timer. Thus, transmission of said second reset request may further include iteratively restarting said timer and transmitting subsequent reset  
30 request code sequences when said timer expires until the encoder and decoder are synchronized.

The communication network typically further includes a plurality of nodes arranged such that a plurality of paths exist  
35 between at least some nodes between which said method is

practiced, and wherein at least one node may communicate with more than one node at a time using different encoding methods to communicate with at least two different nodes, and wherein the timer is shared by said nodes using different  
5 encoding methods.

Where said encoded data includes compressed data and said step of synchronizing the error detect units includes resynchronizing a transmitter at which insertion and  
10 transmitting are performed and a receiver at which receiving the error detect units, the method may include detecting error(s) utilizing the error detection information and the sequence indicators.

15 FIG. 4, numeral 400, is a block diagram of a first embodiment of a system in accordance with the system of the present invention. The system synchronizes an encoder of an encoder error synchronizer (402) and a decoder of a decoder error synchronizer (404) for encoded data transmitted across a  
20 communication network upon error detection. The encoder error synchronizer (402) is operably coupled to receive data and a reset request from the decoder error synchronizer (404), and is used for transmitting encoded data having error detection information and for, upon receiving the reset  
25 request, resetting the encoder. The decoder error synchronizer (404) is operably coupled across the communication network to receive the encoded data, detecting error(s), and, upon detecting error(s), to send a reset request to the encoder error synchronizer (402).

30

Typically, the encoder error synchronizer (402) includes: an encoder (406) that is operably coupled to receive data and to an acknowledgment unit and is used for encoding data and, upon receiving an encoder reset signal from an  
35 acknowledgment unit (414), resetting; an error detect

information generator (408) that is operably coupled to the encoder (406) and is used for receiving the encoded data and for organizing the data into units of predetermined size(s) and providing sequence identifiers for said units of the encoded data, providing error detection information, and for providing the encoded data to an inserter (410); the inserter (410), that is operably coupled to receive the encoded data, the sequence indicators and error detection information and is used for adding to each unit of encoded data a sequence indicator and error detection information to provide error detect units; a transmission unit (412) that is operably coupled to the inserter (410) and is used for transmitting said error detect units across the communication network; and the acknowledgment unit (414) that is operably coupled to receive a reset request from the decoder error synchronizer (404) and is used for, upon receiving the reset request signal, sending a reset signal to the encoder (406) and a reset acknowledgment signal to the inserter (410).

20       The decoder error synchronizer (404) typically includes: a receiving unit (416) that is operably coupled to the encoder error synchronizer (402), typically by means of a communication network, and is used for receiving the error detect units; a stripping unit (418) that is operably coupled to the receiving unit (416) and is used for providing the sequence identifiers, the error detection information and encoded data for each error detect unit and for transmitting a received reset acknowledgment to a synchronizer (424); an error detector (420) that is operably coupled to the stripping unit (418) and is used for detecting error(s) utilizing the error detection information and the sequence indicators and for providing an error detect signal to the synchronizer (424); a decoder (422) that is operably coupled to the error detector (420) and to the synchronizer (424) and is used for decoding data and resetting upon receiving a reset signal from the

synchronizer; and the synchronizer (424) that is operably coupled to the stripping unit (418) and to the error detector (420) for sending the reset signal to the decoder (422) and for sending a reset request to the encoder error synchronizer (402) upon receiving the error detect signal from the error detector (420).

The units of encoded data are typically frames of asynchronous transfer mode (ATM) cells and the communication network is an ATM network.

Error detection information is generally a code sequence added to said unit of encoded data subsequent to encoding the data such as a cyclic redundancy code (CRC), a code sequence other than a CRC wherein the code sequence is calculated from the encoded data, a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, or a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a previous reset. Thus, where a code sequence is based on a size of the unit of encoded data, for example, a code sequence may be based on a sequence number or running byte-count.

When encoding and decoding are performed on a sequence of data frames, the states of the encoder and decoder are often maintained between processing of successive frames without resetting at the beginning of each frame. Therefore, synchronization must be maintained from frame-to-frame. For example, if the communication network drops an entire frame or mis-orders a sequence of frames, synchronization will be lost. Whereas typical CRCs are based entirely on only a single frame, they are only capable of detecting transmission errors which occur within that frame. They are insufficient for the purpose of detecting the type of error in which frames

are lost entirely or mis-ordered. According to the technique of the present invention, for the purpose of detecting loss of synchronization, the error detection information must be based on the current encoded frame and on at least the previous  
5 encoded frame.

In one embodiment, each successive frame in the sequence of encoded frames is associated with the next value of a frame counter, called a sequence number. In another  
10 embodiment, each successive encoded data byte in the sequence of encoded bytes of encoded frames is associated with the next value of a byte counter, called a sequence number. The sequence number for a frame may be concatenated with the CRC for that frame to comprise the error detecting  
15 information for that frame. In another embodiment, the sequence number and the CRC are combined by adding them together to comprise the error detection information. In yet another embodiment, the error detection information is a CRC computed for the current frame, where unlike the common  
20 practice, the CRC is not reset to a fixed initial value at the beginning of the current frame, but instead the CRC is initialized to the value computed from the previous frame. These and other embodiments of the error detection information are chosen to be simple enough to minimize the  
25 cost of implementation, small enough to minimize the cost of transmission over the network, and are sufficiently unique to the particular encoded frame sequence to provide an acceptably high probability of detecting bit-errors and lost or  
misordered frames.

30

The communication network generally includes a plurality of nodes so arranged that a plurality of paths exist between at least some nodes between which said system is

practiced. At least one node may communicate with more than one node at a time.

The encoded data is generally compressed data.

5

The synchronizer may be selected to further include a timer (426) that is operably coupled to the error detector (420) and is used for starting timing upon said detecting of errors and for transmitting a second reset request code sequence over said reverse channel upon failure to receive said request acknowledgment code sequence upon an expiration of said timer.

10

The communication network may be selected to further include a plurality of nodes arranged such that a plurality of paths exist between at least some nodes between which said system is practiced, and wherein at least one node may communicate with more than one node at a time using different encoding methods to communicate with at least two different nodes, and wherein the timer is shared by said nodes using different encoding methods.

15

20

FIG. 5, numeral 500, is a flow chart of a second embodiment of steps in accordance with the method of the present invention. The method synchronizes an encoder and decoder of a communication network upon detecting an error. The method includes, for units of encoded data, the steps of: 1) adding to each unit of encoded data, error detection information based on a predetermined combination of units of encoded data to provide error detect units (502); 2) transmitting said error detect units across the communication network (504); 3) receiving the error detect units (506); 4) detecting error(s) utilizing the error detection information (508), and 5) synchronizing the encoder and decoder upon detecting error(s) (510). The predetermined combination of

25

30

35



units of encoded data may be selected, for example, to be a present unit of encoded data and a preselected number of prior units of encoded data.

5           As described for FIG. 3, the units of encoded data may be selected to be frames of asynchronous transfer mode (ATM) cells and the frames of ATM cells may be transmitted across an ATM communication network.

10           The error detection information typically is a code sequence added to said unit of encoded data subsequent to encoding the data wherein the code sequence is one of: a cyclic redundancy code (CRC), and a code sequence other than a CRC wherein the code sequence is calculated from the  
15           encoded data in accordance with a predetermined scheme.

Further description of particularities of the method of FIG. 6 follows the description of FIG. 3.

20           Although exemplary embodiments are described above, it will be obvious to those skilled in the art that many alterations and modifications may be made without departing from the invention. Accordingly, it is intended that all such alterations and modifications be included within the spirit and  
25           scope of the invention as defined in the appended claims.

We claim:

1. A method for synchronizing an encoder and a decoder for transmission of units of encoded data across a communication network, said method comprising the steps of:
  - 1A) adding to each said unit error detection
  - 5 information based on a current and at least one previous unit to provide error detect units,
  - 1B) transmitting said error detect units across the communication network,
  - 1C) receiving the error detect units,
  - 10 1D) detecting error(s) utilizing the error detection information, and
  - 1E) synchronizing the encoder and decoder upon error detection.

2. The method of claim 1 wherein at least one of 2A-2E:

2A) the units of encoded data are frames of asynchronous transfer mode (ATM) cells, and where selected, wherein the frames of ATM cells are transmitted across an ATM communication network;

2B) said error detection information is a code sequence added to said unit of encoded data subsequent to encoding the data, and where selected, wherein the code sequence is one of:

10 2B1) a cyclic redundancy code (CRC),

2B2) a code sequence other than a CRC wherein the code sequence is calculated from the encoded data,

2B3) a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, and

2B4) a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a previous reset;

2C) the communication network includes a plurality of nodes so arranged that a plurality of paths exist among at least some nodes between which said method is practiced, and where selected, wherein at least one node may communicate with more than one node at a time;

2D) the encoded data comprises compressed data; and

2E) said encoded data comprises compressed data, and wherein said step of synchronizing the encoder and decoder includes resynchronizing a transmitter at which steps 1A-1B are performed and a receiver at which steps 1C-1E are performed.

3. The method of claim 1 wherein upon the decoder's detecting an error, the decoder's transmitting a reset request to the encoder, and

where the reset request code sequence is received at the encoder, resetting the encoder, and

where each step of synchronizing the encoder and decoder further includes one of 3A-3B:

5           3A) where the encoder transmits an acknowledgment code sequence over said communication network to acknowledge reception of said reset request code sequence and the acknowledgment code sequence is received, resetting the decoder such that the decoder is synchronized  
10 with the encoder, and

          3B) where the decoder is reset upon the decoding of each encoded data unit until a received unit successfully passed error detection, and where selected,

15           3C) wherein said step of synchronizing the encoder and decoder upon detecting error(s) further includes one of 3C1 and 3C2:

          3C1) transmitting a second reset request code sequence over a reverse channel upon failure to receive  
20 said acknowledgment code sequence upon an expiration of a timer, and

          3C2) transmitting a second reset request code sequence over said reverse channel upon failure of at least one received unit to successfully pass error detection  
25 upon an expiration of said timer; and where further selected,

          3D) where transmission of said second reset request further includes iteratively restarting said timer and transmitting subsequent reset request code sequences when  
30 said timer expires until the encoder and decoder are synchronized, and where further selected,

          3E) wherein the communication network further includes a plurality of nodes arranged such that a plurality of  
35 paths exist between at least some nodes between which said

method is practiced, and wherein at least one node may communicate with more than one node at a time using different encoding methods to communicate with at least two different nodes, and wherein the timer is shared by the node

5 using different encoding methods.

4. A system for synchronizing an encoder of an encoder error synchronizer and a decoder of a decoder error synchronizer upon detection of error(s) in transmission of units of encoded data across a communication network, said  
5 system comprising:

4A) an encoder error synchronizer, operably coupled to receive data and a reset request from the decoder error synchronizer, for transmitting encoded data having error detection information and for, upon receiving the reset  
10 request, resetting the encoder, and

4B) a decoder error synchronizer, operably coupled to receive the encoded data, detecting error(s), and, upon detecting error(s), sending a reset request to the encoder error synchronizer.

15

5. The system of claim 4, wherein at least one of 5A-5F:

5A) the encoder error synchronizer comprises 5A1-5A5:

5A1) an encoder, operably coupled to receive data and to an acknowledgment unit, for encoding data and, upon receiving an encoder reset signal from the acknowledgment unit, resetting,

5A2) an error detect information generator, operably coupled to the encoder, for receiving the encoded data and for organizing the data into units of predetermined size(s) and providing sequence identifiers for said units of the encoded data, providing error detection information, and for providing the encoded data to an inserter,

5A3) the inserter, operably coupled to receive the encoded data, the sequence indicators and error detection information, for adding to each unit of encoded data a sequence indicator and error detection information to provide error detect units,

5A4) a transmission unit, operably coupled to the inserter, for transmitting said error detect units across the communication network, and

5A5) the acknowledgment unit, operably coupled to receive a reset request from the decoder error synchronizer, for, upon receiving the reset request signal, sending a reset signal to the encoder and a reset acknowledgment signal to the inserter;

5B) the units of encoded data are frames of asynchronous transfer mode (ATM) cells;

5C) the communication network is an ATM network;

5D) said error detection information is a code sequence added to said unit of encoded data subsequent to encoding the data, and where selected, wherein the code sequence is one of 5D1-5D4:

5D1) a cyclic redundancy code (CRC),

5D2) a code sequence other than a CRC wherein the code sequence is calculated from the encoded data,

5D3) a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, and

5 5D4) a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a previous reset;

5E) the communication network includes a plurality of nodes so arranged that a plurality of paths exist between at least some nodes between which said system is practiced, and  
10 where selected, wherein at least one node may communicate with more than one node at a time;

5F) the encoded data comprises compressed data.

15 6. The system of claim 4 wherein the decoder error synchronizer comprises 6A-6E:

6A) a receiving unit, operably coupled to the encoder error synchronizer, for receiving the error detect units,

20 6B) a stripping unit, operably coupled to the receiving unit, for providing the sequence identifiers, the error detection information and encoded data for each error detect unit and for transmitting a received reset acknowledgment to a synchronizer,

25 6C) an error detector, operably coupled to the stripping unit, for detecting error(s) utilizing the error detection information and the sequence indicators and for providing an error detect signal to the synchronizer,

30 6D) a decoder, operably coupled to the error detector and to the synchronizer, for decoding data and resetting upon receiving a reset signal from the synchronizer, and

35 6E) the synchronizer, operably coupled to the stripping unit and to the error detector, for sending the reset signal to the decoder and for sending a reset request to the



- encoder error synchronizer on a reverse channel upon receiving the error detect signal from the error detector, and where selected, wherein the synchronizer further includes a timer, operably coupled to the error and sequence detector, for
- 5 starting timing upon said detecting of errors and for transmitting a second reset request code sequence over said reverse channel upon failure to receive said request acknowledgment code sequence upon an expiration of said timer, and where further selected, wherein the communication
- 10 network further includes a plurality of nodes arranged such that a plurality of paths exist between at least some nodes between which said system is practiced, and wherein at least one node may communicate with more than one node at a time using different encoding methods to communicate with
- 15 at least two different nodes, and wherein the timer is shared by said nodes using different encoding methods.

7. A method for synchronizing an encoder and a decoder for transmission of predetermined units of data across a communication network, said method comprising the steps of:

- 5 7A) adding to each unit of encoded data, error detection information based on a predetermined combination of units of encoded data to provide error detect units,
- 7B) transmitting said error detect units across the communication network,
- 7C) receiving the error detect units,
- 10 7D) detecting error(s) utilizing the error detection information, and
- 7E) synchronizing the encoder and decoder upon detecting error(s).

8. The method of claim 7 wherein at least one of 8A-8F:

8A) the units of encoded data are frames of asynchronous transfer mode (ATM) cells;

5 8B) the frames of ATM cells are transmitted across an ATM communication network;

8C) said error detection information is a code sequence added to said unit of encoded data subsequent to encoding the data;

10 8D) the code sequence is one of 8D1-8D4:

8D1) a cyclic redundancy code (CRC),

8D2) a code sequence other than a CRC wherein the code sequence is calculated from the encoded data;

15 8D3) a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, and

8D4) a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a previous reset;

20 8E) the encoded data comprises compressed data; and

8F) the communication network further includes a plurality of nodes arranged such that a plurality of paths exist between at least some nodes between which said method is practiced, and wherein at least one node may communicate with more than one node at a time using different encoding methods to communicate with at least two different nodes, and wherein the timer is shared by the node using different encoding methods.

30 9. The method of claim 7 wherein the communication network includes a plurality of nodes so arranged that a plurality of paths exist among at least some nodes between which said method is practiced, and where selected, wherein at least one node may communicate with more than one node at a time.

35

10. The method of claim 7 wherein upon the decoder's detecting an error, the decoder's transmitting a reset request to the encoder, and

5       where the reset request code sequence is received at the encoder, resetting the encoder, and

      where each step of synchronizing the encoder and decoder further includes one of:

10       10A) where the encoder transmits an acknowledgment code sequence over said communication network to acknowledge reception of said reset request code sequence and the acknowledgment code sequence is received, resetting the decoder such that the decoder is synchronized with the encoder, and

15       10B) where the decoder is reset upon the decoding of each encoded data unit until a received unit successfully passed error detection; and where selected,

20       wherein said step of synchronizing the encoder and decoder upon detecting error(s) further includes one of 10C and 10D:

25       10C) transmitting a second reset request code sequence over a reverse channel upon failure to receive said acknowledgment code sequence upon an expiration of a timer, and

30       10D) transmitting a second reset request code sequence over said reverse channel upon failure of at least one received unit to successfully pass error detection upon an expiration of said timer; and where further selected, where transmission of said second reset request further includes iteratively restarting said timer and transmitting subsequent reset request code sequences when said timer expires until the encoder and decoder are synchronized.

35

## AMENDED CLAIMS

[received by the International Bureau on 03 February 1995 (03.02.95); original claims 1, 4, 7 amended; remaining claims unchanged (9 pages)]

1. (Amended) A method for synchronizing an encoder and a decoder for transmission of units of encoded data across a communication network, said method comprising the steps of:
  - 1A) adding to each said unit error detection information  
5 based on a current and at least one previous unit to provide error detect units,
  - 1B) transmitting said error detect units across the communication network,
  - 1C) receiving the error detect units,
  - 10 1D) detecting error(s) utilizing the error detection information, and
  - 1E) synchronizing the encoder and decoder upon error detection,
  - 1F) wherein said error detection information is a code  
15 sequence added to said unit of encoded data subsequent to encoding the data, and where selected, wherein the code sequence is one of:
    - 1F1) a cyclic redundancy code (CRC),
    - 1F2) a code sequence other than a CRC wherein the  
20 code sequence is calculated from the encoded data,
    - 1F3) a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, and
    - 1F4) a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a  
25 previous reset;
- and
  - 1G) the communication network includes a plurality of nodes so arranged that a plurality of paths exist among at least some nodes between which said method is practiced, and where  
30 selected, wherein at least one node may communicate with more than one node at a time;
  - 1H) the encoded data comprises compressed data;

and

11) said encoded data comprises compressed data, and wherein said step of synchronizing the encoder and decoder includes resynchronizing a transmitter at which steps 1A-1B are performed and a receiver at which steps 1C-1E are performed, and

1J) wherein upon the decoder's detecting an error, the decoder's transmitting a reset request to the encoder, and where the reset request code sequence is received at the encoder, resetting the encoder, and

where each step of synchronizing the encoder and decoder further includes one of 1J1-1J2:

1J1) where the encoder transmits an acknowledgment code sequence over said communication network to acknowledge reception of said reset request code sequence and the acknowledgment code sequence is received, resetting the decoder such that the decoder is synchronized with the encoder, and

1J2) where the decoder is reset upon the decoding of each encoded data unit until a received unit successfully passed error detection.

2. The method of claim 1 wherein at least one of 2A-2D:

2A) the units of encoded data are frames of asynchronous transfer mode (ATM) cells, and where selected, wherein the frames of ATM cells are transmitted across an ATM communication network;

2B) the communication network includes a plurality of nodes so arranged that a plurality of paths exist among at least some nodes between which said method is practiced, and where selected, wherein at least one node may communicate with more than one node at a time;

2C) the encoded data comprises compressed data;  
and

2D) said encoded data comprises compressed data, and  
wherein said step of synchronizing the encoder and decoder  
5 includes resynchronizing a transmitter at which steps 1A-1B are  
performed and a receiver at which steps 1C-1E are performed.

3. The method of claim 1

3A) wherein said step of synchronizing the encoder  
10 and decoder upon detecting error(s) further includes one of 3C1  
and 3C2:

3A1) transmitting a second reset request code  
sequence over a reverse channel upon failure to receive said  
acknowledgment code sequence upon an expiration of a timer, and

15 3A2) transmitting a second reset request code  
sequence over said reverse channel upon failure of at least one  
received unit to successfully pass error detection upon an  
expiration of said timer;  
and where further selected,

20 3B) where transmission of said second reset request  
further includes iteratively restarting said timer and  
transmitting subsequent reset request code sequences when said  
timer expires until the encoder and decoder are synchronized,  
and where further selected,

25 3C) wherein the communication network further  
includes a plurality of nodes arranged such that a plurality of  
paths exist between at least some nodes between which said  
method is practiced, and wherein at least one node may  
communicate with more than one node at a time using different  
30 encoding methods to communicate with at least two different  
nodes, and wherein the timer is shared by the node using  
different encoding methods.

4. (Amended) A system for synchronizing an encoder of an encoder error synchronizer and a decoder of a decoder error synchronizer upon detection of error(s) in transmission of units  
5 of encoded data across a communication network, said system comprising:

4A) an encoder error synchronizer, operably coupled to receive data and a reset request from the decoder error synchronizer, for transmitting encoded data having error  
10 detection information and for, upon receiving the reset request, resetting the encoder, and

4B) a decoder error synchronizer, operably coupled to receive the encoded data, detecting error(s), and, upon detecting error(s), sending a reset request to the encoder error  
15 synchronizer,  
and wherein at least one of 4C-4D:

4C) the encoder error synchronizer comprises 4C1-4C5:

4C1) an encoder, operably coupled to receive data and to an acknowledgment unit, for encoding data and, upon  
20 receiving an encoder reset signal from the acknowledgment unit, resetting,

4C2) an error detect information generator, operably coupled to the encoder, for receiving the encoded data and for organizing the data into units of predetermined size(s) and  
25 providing sequence identifiers for said units of the encoded data, providing error detection information, and for providing the encoded data to an inserter,

4C3) the inserter, operably coupled to receive the encoded data, the sequence indicators and error detection  
30 information, for adding to each unit of encoded data a sequence indicator and error detection information to provide error detect units,



4C4) a transmission unit, operably coupled to the inserter, for transmitting said error detect units across the communication network, and

5 4C5) the acknowledgment unit, operably coupled to receive a reset request from the decoder error synchronizer, for, upon receiving the reset request signal, sending a reset signal to the encoder and a reset acknowledgment signal to the inserter;

4D) said error detection information is a code sequence added to said unit of encoded data subsequent to encoding the data, and where selected, wherein the code sequence is one of  
10 4D1-4D4:

4D1) a cyclic redundancy code (CRC),

4D2) a code sequence other than a CRC wherein the code sequence is calculated from the encoded data,

15 4D3) a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, and

4D4) a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a previous reset.

20

5. The system of claim 4, wherein at least one of 5A-5D:

5A) the units of encoded data are frames of asynchronous transfer mode (ATM) cells;

5B) the communication network is an ATM network;

25 5C) the communication network includes a plurality of nodes so arranged that a plurality of paths exist between at least some nodes between which said system is practiced, and where selected, wherein at least one node may communicate with more than one node at a time;

30 5D) the encoded data comprises compressed data.

6. The system of claim 4 wherein the decoder error synchronizer comprises 6A-6E:

6A) a receiving unit, operably coupled to the encoder error synchronizer, for receiving the error detect units,

5 6B) a stripping unit, operably coupled to the receiving unit, for providing the sequence identifiers, the error detection information and encoded data for each error detect unit and for transmitting a received reset acknowledgment to a synchronizer,

10 6C) an error detector, operably coupled to the stripping unit, for detecting error(s) utilizing the error detection information and the sequence indicators and for providing an error detect signal to the synchronizer,

15 6D) a decoder, operably coupled to the error detector and to the synchronizer, for decoding data and resetting upon receiving a reset signal from the synchronizer, and

6E) the synchronizer, operably coupled to the stripping unit and to the error detector, for sending the reset signal to the decoder and for sending a reset request to the  
20 encoder error synchronizer on a reverse channel upon receiving the error detect signal from the error detector, and where selected, wherein the synchronizer further includes a timer, operably coupled to the error and sequence detector, for starting timing upon said detecting of errors and for transmitting a  
25 second reset request code sequence over said reverse channel upon failure to receive said request acknowledgment code sequence upon an expiration of said timer, and where further selected, wherein the communication network further includes a plurality of nodes arranged such that a plurality of paths exist  
30 between at least some nodes between which said system is practiced, and wherein

at least one node may communicate with more than one node at a time using different encoding methods to communicate with at least two different nodes, and wherein the timer is shared by said nodes using different encoding methods.

5

7. (Amended) A method for synchronizing an encoder and a decoder for transmission of predetermined units of data across a communication network, said method comprising the steps of:

7A) adding to each unit of encoded data, error detection  
10 information based on a predetermined combination of units of encoded data to provide error detect units,

7B) transmitting said error detect units across the communication network,

7C) receiving the error detect units,

15 7D) detecting error(s) utilizing the error detection information, and

7E) synchronizing the encoder and decoder upon detecting error(s),

20 wherein said error detection information is a code sequence added to said unit of encoded data subsequent to encoding the data;

and wherein upon the decoder's detecting an error, the decoder's transmitting a reset request to the encoder, and

25 where the reset request code sequence is received at the encoder, resetting the encoder, and

where each step of synchronizing the encoder and decoder further includes one of:

7F) where the encoder transmits an acknowledgment  
code sequence over said communication network to acknowledge  
30 reception of said reset request code sequence and the acknowledgment code sequence is received, resetting the decoder such that the decoder is synchronized with the encoder, and

7G) where the decoder is reset upon the decoding of each encoded data unit until a received unit successfully passed error detection;  
and where selected,

5 wherein said step of synchronizing the encoder and decoder upon detecting error(s) further includes one of 7H and 7I:

7H) transmitting a second reset request code sequence over a reverse channel upon failure to receive said acknowledgment code sequence upon an expiration of a timer, and

10 7I) transmitting a second reset request code sequence over said reverse channel upon failure of at least one received unit to successfully pass error detection upon an expiration of said timer;

and where further selected, where transmission of said second reset request further includes iteratively restarting said timer and transmitting subsequent reset request code sequences when said timer expires until the encoder and decoder are synchronized.

20

8. The method of claim 7 wherein at least one of 8A-8F:

8A) the units of encoded data are frames of asynchronous transfer mode (ATM) cells;

25 8B) the frames of ATM cells are transmitted across an ATM communication network;

8C) the code sequence is one of 8C1-8C4:

8C1) a cyclic redundancy code (CRC),

8C2) a code sequence other than a CRC wherein the code sequence is calculated from the encoded data,


30 8C3) a code sequence other than a CRC wherein the code sequence is based on a size of the unit of encoded data, and

8C4) a code sequence other than a CRC wherein the code sequence is based on the number of said data units since a previous reset;


8D) the encoded data comprises compressed data; and

5        8E) the communication network further includes a plurality of nodes arranged such that a plurality of paths exist between at least some nodes between which said method is practiced, and wherein at least one node may communicate with more than one node at a time using different encoding methods to communicate  
10 with at least two different nodes, and wherein the timer is shared by the node using different encoding methods.


9.     The method of claim 7 wherein the communication network includes a plurality of nodes so arranged that a plurality of paths  
15 exist among at least some nodes between which said method is practiced, and where selected, wherein at least one node may communicate with more than one node at a time.

**FIG. 1**100

—PRIOR ART—

**FIG. 2**200

2 / 4

*FIG. 3*300

3/4





FIG. 4

400



4/4

*FIG. 5*500

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US94/12033

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :G06F 11/10; H04L 12/56  
US CL :371/42; 370/94.1

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 371/42, 32, 33, 47.1, 37.1; 370/94.1, 94.2, 94.3

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
none

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
none

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 5,130,993 (Gutman et al.) 14 July 1992, cols 1-5.	1-10
Y	US, A, 5,168,497 (Ozaki et al.) 01 December 1992, cols 1-2.	1-10
A	US, A, 5,230,002 (Yamashita et al.) 20 July 1993, cols 4 and 5.	1-10
A	US, A, 4,893,339 (Bright et al.) 09 January 1990, see figure 2.	1-10
A	US, A, 4,779,275 (Yoshimoto) 18 October 1988, see figure 2 and col. 3.	1-10
A	US, A, 4,577,313 (Sy) 18 March 1986, see figure 4 and col. 7.	1-10

<input type="checkbox"/> Further documents are listed in the continuation of Box C.	<input type="checkbox"/> See patent family annex.
<p>* Special categories of cited documents:</p> <p>*A* document defining the general state of the art which is not considered to be part of particular relevance</p> <p>*E* earlier document published on or after the international filing date</p> <p>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>*O* document referring to an oral disclosure, use, exhibition or other means</p> <p>*P* document published prior to the international filing date but later than the priority date claimed</p>	<p>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>*Z* document member of the same patent family</p>

Date of the actual completion of the international search 01 DECEMBER 1994	Date of mailing of the international search report JAN 23 1995
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230	Authorized officer ROY ENVALL JR. Telephone No. (703) 305-9706

Form PCT/ISA/210 (second sheet)(July 1992)\*